

HD-IP IR HIGH SPEED 36X Zoom DOME



Features:

- * Support P2P function
- * 7" half metal body construction, IP66
- * Optional function: Alarm, Audio
- * 10pcs Array 42Mil Led+2PCS Laser Led, IR range up to 180M
- * ONVIF2.4 ; Compatible with HIKVISION, DAHUA, XM, Video park NVR .etc
- * Compatible with CMS, UC2, Milestone, NUUO and AXXON platform.etc
- * Intelligent IR illumination & power consumption is variable, dependant the zoom factor

Model Number: VAITHSP01

Specification:

| Camera | |
|------------------------------------|---|
| Sensor | 3516D 5MP AR0521 |
| Output pixel | 2592x1944/15fps, 2592x1520/25fps |
| Lens | 36X f=4.6~165.6mm |
| BLC | Support |
| AGC | Auto/Manual |
| WB | Indoor/Outdoor/Auto/Manual |
| DNR | 2DNR, 3DNR |
| WDR | DWDR |
| S/N Ratio | ≥50dB |
| Dome | |
| Communications Protocol | TCP/IP, HTTP, NTP, IGMP, DHCP, UDP, SMTP, RTP, RTSP, ARP, DDNS, DNS, HTTPS, P2P |
| Software Control | IE, CMS, Management Platform, P2P |
| Mobile View(optional) | Android , iPhone |
| Rotation range | Pan:0~360°, Tilt:0~93° |
| Rotation speed | Pan:0~200°/s, Tilt:0~120°/s |
| medium rotation speed for optional | Pan:0~60°/s, Tilt:0~45°/s |
| Auto Flip | Horizontal 180°, Vertical 93° |

| | |
|-----------------------|---|
| Preset Points | 220pcs presets (dwell time 01-60s interval available) |
| A-B scan | User programmabel(scan speed 1-64 levels setting available) |
| Guard Tours | 3 groups(Max.16 points, dwell time user selectable) |
| video compression | H.264/H.265M-JPEG |
| audio compression | G711~PCM |
| Operating temperature | -40℃~+60℃ |
| Operation menu | English |
| Power | DC 12V 4A/DC 12V 3A |
| Consumption | ≤25W |
| Lightning Protection | Transient voltage 6000V |
| Related validation | IP66,CE,FCC,RoHs |

IR parameters

| | |
|---------------------------------|--|
| Auto Control IR LED | PWM |
| LEDs | 10pcs Array 42Mil IR Led+2PCS Laser Led |
| IR distance | Up to 180 meters |
| Support ambient light detection | IR illumination on 1-9 grades selectable |

